

DOOR VIEWERS

SECURITY HARDWARE

DOOR VIEWERS




B02

- Solid brass door viewer
- Acrylic optical lens
- Individually boxed

| MODEL | FINISH | DOOR THICKNESS | ø BORE | FIRE RATING | VISION ANGLE | /BOX |
|-------|----------|------------------------|--------|-------------|--------------|------|
| B02 | C3, C26D | 1 3/8–2 1/4 (35–57) | 12 mm | — | 160° | 25 |
| B03 | C3, C26D | | 14 mm | — | 180° | 25 |
| B04 | C3, C26D | | 16 mm | — | 200° | 10 |

IN (MM)



DV160



DV180, DV200

- Solid brass door viewer
- cULus 20 minute fire rating for labelled fire doors
- Polished glass and acrylic optical lenses
- Individually boxed

| MODEL | FINISH | DOOR THICKNESS | ø BORE | FIRE RATING | VISION ANGLE | /BOX |
|-------|------------|------------------------|--------|-------------|--------------|------|
| DV160 | 3, 26, 26D | 1 3/8–2 (35–51) | 12 mm | 20 min | 160° | 25 |
| DV180 | 26D, 19 | | 14 mm | 20 min | 180° | 25 |
| DV200 | 26D | 1 3/8–2 1/4 (35–57) | 14 mm | 20 min | 200° | 10 |

IN (MM)



DV1012SRG



DV1012BRQ



DV1012BLQ

- Solid brass door viewer
- cULus 90 minute fire rating for labelled fire doors
- Polished glass and quartz lens
- Individually boxed

| MODEL | FINISH | DOOR THICKNESS | ø BORE | FIRE RATING | VISION ANGLE | /BOX |
|-----------|-------------|----------------------------|--------|-------------|--------------|------|
| DV1012SRG | 15, 19, 26D | 1 1/16–1 1/16 (17.5–27) | 12 mm | 90 min | 160° | 25 |
| DV1012BRQ | 26 | 1 3/8–2 (35–51) | 12 mm | 90 min | 160° | 42 |
| DV1012BLQ | 19, 26 | 1 3/4–2 1/4 (44.5–57) | 12 mm | 90 min | 200° | 25 |
| DV1014BLQ | 15, 19, 26D | | 14 mm | 90 min | 200° | 25 |

IN (MM)