



NOTE: F1C is available by special order; minimum order quantities and additional delivery times may be required.

Type	• Cylindrical lock	Chassis	• Concealed mounting plate and screws
Certifications	• Certified ANSI/BHMA A156.2, Series 4000, Grade 1 • cULus listed, 3hr fire-rating • UL 10C Positive Pressure Rating • Meets ADA requirements • 10 Year limited warranty		• Fixed security posts
			• Lever clutch release
Door Thickness	• 1⅜–2¼" (35–57 mm)	Preparation	• Cross bore: 2⅞" (54 mm)
			• Edge bore: 1" (25.4 mm)
Handing	• Non handed	Cylinder	• Solid brass, 6-pin
Backset	• 2¾" (70 mm)		• Schlage "C" keyway, 2 keys
	• 2⅜" (60 mm) – available		• Removable, rekeyable
Spring Latch	• Stainless steel, ½" (12.7 mm) throw		• Small format interchangeable core (SFIC) model – available*
	• Deadlatch, ¾" (19 mm) throw – available	Other keyways and keying options available, including CX5 high security. (*) BEST® and CX5® cores sold separately.	
Faceplate	• Mortise type, square corners	Functions	10 Passage
	• 1⅞x2¼" (28.5x57 mm)		17 Dummy, single
Strike	• ASA Strike		42 Privacy
		Lever Style	C–Curved return
Trim	• Solid, pressure cast heavy duty lever	Finish	26D–Satin chrome
	• Lever secured by additional set screw		Other finishes available by special order
	• Brass rose		
	• Rose diameter: 3½" (89mm)		

F1	C	53	26D	238
SERIES	STYLE	FUNCTION	FINISH	OPTION¹


(1) OPTION: 238 2-3/8IN (60MM) BACKSET

SELECTION GUIDE

SERIES	STYLE	FUNCTION ¹		FINISH ¹	/ CASE
F1	C	10	Passage	26D	6
F1	C	17	Dummy, single	26D	12
F1	C	42	Privacy	26D	6
F1	C	53	Entry ➡	26D	6
F1	C	70	Classroom ➡	26D	6
F1	C	80	Storeroom ➡	26D	6

(1) OTHER FINISHES AND FUNCTIONS AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED.

➡ KEYED FUNCTION; FULL KEYING SERVICES AVAILABLE.



		A	B	C	D*
F1C		3½ (89)	4½ (114)	2½ (63.3)	⅝ (16)

IN (MM)

(*) DIMENSION MAY VARY DUE TO DOOR THICKNESS.

PARTS & ACCESSORIES



9106

T-Strike, square corners:
1⅝x2¾" (28.5x70 mm)

9106NH

T-Strike, no hole; square corners:
1⅝x2¾" (28.5x70 mm)



ASA-T

ASA strike with adjustable tab

ASANH

ASA strike, no hole



F1001

Passage latch: 2⅜" (60 mm) backset,
1⅝x2¼" (28.5x57 mm) faceplate



F1010

Privacy latch: 2⅜" (60 mm) backset,
1⅝x2¼" (28.5x57 mm) faceplate



F1005

Deadlatch: 2⅜" (60 mm) backset,
1⅝x2¼" (28.5x57 mm) faceplate



F1DL234-34

Deadlatch: 2⅜" (70 mm) backset, ¾" (19 mm)
throw. 1⅝x2¼" (28.5x57 mm) faceplate
*For use in double door or electric strike
applications*

