

PF102 SERIES

HYDRAULIC PATCH FITTING CLOSER



1
YEAR

-
- Certifications** • 1 Year limited warranty
- Panel Thickness** • $\frac{5}{16}$ – $\frac{1}{2}$ " (8–13 mm)
- Max. Door Width** • 39" (1000 mm)
- Max. Door Weight** • 220 lbs (100 kg)
- Max. Door Height** • For $\frac{5}{16}$ " (8 mm) glass: 84" (2134 mm)
• For $\frac{1}{2}$ " (13 mm) glass: 108" (2743 mm)
- Body Material** • Machined aluminum
- Mechanism** • Hydraulic spring
- Fluid** • All weather hydraulic fluid
- Adjustments** • Sweep speed adjustment
• Latching speed adjustment
• Door adjustments:
» Vertical / horizontal: $\pm \frac{1}{32}$ " (1 mm)
» CW /CCW: $\pm 2^\circ$
- Cover** • Stainless steel snap-on cover
- Handing** • Non-handed
- Opening** • Double acting
• 170° Maximum
• 90° Hold open – option
- Mounting** • Floor surface mounted
- Hardware** • Screws and masonry anchors
- Finish** 630–Satin stainless steel; 19–Matte black*
- (*) Special order–may require additional lead time and/or minimum order quantities


PF102DC – 630
MODEL FINISH

SEE SELECTION GUIDE FOR DETAILS



SELECTION GUIDE

MODEL	WEIGHT CAPACITY ¹	MAX. DOOR WIDTH ²		MAX. DOOR HEIGHT ³	BACKCHECK	HOLD OPEN	FINISH
		INTERIOR	EXTERIOR				
PF102DC	220	39	—	84 or 108	—	—	630, 19*
PF102DCHO	(100)	(1000)	—	(2134 or 2743)	—	●	

(1) DOOR WEIGHT CAPACITY RANGE IN POUNDS (KILOGRAMS) (2) MAXIMUM DOOR WIDTH IN INCHES (MILLIMETRES)
 (3) FOR 5/16" (8MM) GLASS THICKNESS DO NOT EXCEED 84" (2134MM) (*)SPECIAL ORDER FINISH



DOOR CLOSER
PF102DC / DCHO



MODEL	A	B	C	D	E	F	G
PF102DC	2 ³ / ₄	7 ³ / ₁₆	1 ²¹ / ₃₂	4 ⁷ / ₈	1/2	2 ⁵ / ₁₆	1 ¹³ / ₃₂ to 1/2
PF102DCHO	(70)	(182)	(42)	(124)	(12.7)	(58)	(10 to 13)

IN (MM)

PARTS & ACCESSORIES



PF121
Top door patch fitting with extended covers. Available in matching finishes. See 04.400 for other glass patch fittings.



Patch Fitting Door Locks

See 01.500 for a complete list of available patch fitting door locks.



PF120TP1
Top pivot, surface mounted. Available in matte black (19) finish.



PF120TP2
Top walking pivot. Mortised, with adjustable pivot.



PF165CM
Ceiling mounted door stop. Cast stainless steel. Includes mounting screws and plastic anchors.



Architectural Door Pulls

See 06.010 for a complete list of available architectural stainless steel door pulls.

Including:
 – Mitered door pulls
 – Ladder type door pulls
 – Offset door pulls

